

Ficha Técnica de Producto

DERMOCAR WAX

Hydrophobic wax



DESCRIPTION

Hydrophobic wax for automatic car wash installations, automatic dragging comboyes, high-pressure laundries, etc.

It avoids the stains produced by the lime of the water on the paint and helps drying.

FORM OF USE

Depending on the quality of the rinse water and the volume of water used, its dosage will vary between 1 and 10 g / liter of water.

Protect the product against possible frost.

TECHNICAL CHARACTERISTICS

Appearance: Liquid.

Color: Brown

Smell: Characteristic

pH (1%): 5 ± 0.5

Density: 1.01 ± 0.05 g / cc

Solubility in water: Soluble

COMPOSITION

Cationic, non-ionic surfactants and amines.

PRESENTATION

Plastic containers:

FORMAT	25 Kg
CODE	014WAX25

SECURITY/TOXICOLOGY

Causes burns. Wear suitable protective clothing, gloves and eye/face protection.

Keep out of the reach of children.

ADDITIONAL INFORMATION

INDUSTRIAL PRODUCT. PROFESSIONAL USE.

Commercial information. For the handle and employment of product, follow the indications of the label and the MSDS.

To resolve any doubt, can contact with our Technical Department.

The valid version of this document is available only in the web www.dermo.com.