

Ficha Técnica de Producto

MOTORNET

Engines degreaser



DESCRIPTION

Degreaser for explosion engines and not painted surfaces, which can be mixed or emulsified in water at any proportions. It degreases engines and metallic spare parts in general, emulsifying and dissolving grease, mud, lampblack and other substances adhered. It can also be used to scour floors of workshops, petrol stations, etc.

FORM OF USE

Depending on filthiness to treat can be diluted in water from 20 to 50%.
It can be applied by pulverisation, by pressure or with brush for better introduction of Motornet on grease layers. After about 5 minutes of application, rinse with abundant water (if it is possible by pressure).
It is not aggressive against rubber, cables, ...

TECHNICAL CHARACTERISTICS

Aspect: Liquid.
Color: Colorless.
Smell: Characteristic.
pH pure : 9.5 – 10.5.
Density: 0.99 – 1.01 g /cc.
Active Substance concentration 18 -22 %

COMPOSITION

Anionic and non ionic tensioactives, sequestrants, corrosion inhibitors.

PRESENTATION

Plastic containers:

FORMAT	5Kg
CODE	014MOT05

SECURITY/TOXICOLOGY

Irritating to eyes.
Keep out of the reach of the children.

ADDITIONAL INFORMATION

INDUSTRIAL PRODUCT. PROFESSIONAL USE.

Commercial information. For the handle and employment of product, follow the indications of the label and the MSDS.
To resolve any doubt, can contact with our Technical Department.
The valid version of this document is available only in the web www.dermo.com.

Revision: 004 Date: 29/10/12