

LIMCAL

Descaler



DESCRIPTION

Powerful removal of incrustations for either hot or cold water circuits of dishwashers, washing machines... Removes limescale and oxide incrustations. Effective for use in final cleaning of building works and swimming pools (cement residues, environmental dirt, salt, limescale and rust stains) and cleans the joints of the tiles.

FORM OF USE

Dishwashers: Do an empty wash cycledosing from 5% to 10%. Repeat the process every 15 days for optimum machine maintenance.

Dishes recovery: Dilute the product from 3 to 5% in a bowl of water. Immerse dishes from 5 to 10 minutes. Rinse with water.

Cleaning of building works: Check that the material is resistant to acids (stoneware, ceramic, tile, granite, slate). Dilute between 40 and 60% in water. Apply and rub the surface with a brush. Rinse with water to neutral pH. Do not use on marble or limestone.

Building Equipment: To remove residues of cement from mixers, wheelbarrows ... use diluted from 20 to 50%.

Joints of the tiles: Dilute 30 to 40% water. Apply on the joints and immediately rub with a brush or sponge. After application neutralize with water.

TECHNICAL CHARACTERISTICS

Aspect: Opaque liquid.

Colour: White.

Smell: Beer almond.

pH pure: <1

Density: 1,05 – 1,07 g/cc

Active substance concentration: 17 – 20 %

COMPOSITION

Inorganic acids, fragrance.

PRESENTATION

Plastic containers:

FORMAT	1 kg	5 kg
CODE	003LIM01	003LIM05

SECURITY/TOXICOLOGY

Causes severe skin burns and eye damage.

Wear protective gloves/protective clothing/eye protection.

ADDITIONAL INFORMATION

INDUSTRIAL PRODUCT. PROFESSIONAL USE.

Commercial information. For the handle and use of product, follow the indications of the label and the MSDS.

To resolve any doubt, contact with our Technical Department: tecnico@dermo.com. The valid version of this document is available only in the web www.dermo.com.

Revision: 008 Date: 10/03/25